Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	3658	(encrypt$4 encod$3 encipher$8 cipher$9) near4 (public$2 share$2 common) near2 key$1	USPAT; IBM_TDB	OR	OFF	2005/05/09 11:22
L2	15240	(recipient$1 reciev$4 user$2 client$2) near2 key$1	USPAT; IBM_TDB	OR	OFF	2005/05/09 11:23
L3	1338	(recipient$1 reciev$4 user$2 client$2) near3 (private$2 secret$2) near2 key$1	USPAT; IBM_TDB	OR	OFF	2005/05/09 11:30
L4	1041	l1 and l3	USPAT; IBM_TDB	OR	OFF	2005/05/09 11:30
L5	376	(grantor$2 sender$2) near3 (private$2 secret$2) near2 key$1	USPAT; IBM_TDB	OR	OFF	2005/05/09 11:31
L6	193	l4 and l5	USPAT; IBM_TDB	OR	OFF	2005/05/09 11:31
L7	40	l6 and (elgamal)	USPAT; IBM_TDB	OR	OFF	2005/05/09 12:09
L10	4545	((713/200) or (713/201) or (380/28) or (380/29) or (380/30) or (380/228) or (380/259) or (380/268) or (380/282) or (380/245) or (380/44)).CCLS.	USPAT; IBM_TDB	OR	OFF	2005/05/09 12:08
L11	1280	l1 and l10	USPAT; IBM_TDB	OR	OFF	2005/05/09 12:08
L12	468	l3 and l11	USPAT; IBM_TDB	OR	OFF	2005/05/09 12:08
L13	102	l5 and l12	USPAT; IBM_TDB	OR	OFF	2005/05/09 12:08
L14	81	l13 not l7	USPAT; IBM_TDB	OR	OFF	2005/05/09 12:09

09/464, 703

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	2944	(encrypt$4 encipher$8 cipher$8) near3 ((public$2 common) near key$1)	USPAT; IBM_TDB	OR	OFF	2005/05/10 16:10
L2	1405	(recipient$1 receiver$1 user$1 client$1) near3 ((secret$2 private$1) near key$1)	USPAT; IBM_TDB	OR	OFF	2005/05/10 16:11
L3	395	(grant$3 sender$1) near3 ((secret$2 private$1) near key$1)	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:41
L4	219	l1 and l2 and l3	USPAT; IBM_TDB	OR	OFF	2005/05/10 16:11
L5	39	l4 and (re-encrypt$4 reencrypt$4 re-encipher$8 reencipher$8 re-cipher$7 recipher$8)	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:36
L6	25544	(secret$2 private$1 shared same$1 combin$6) near3 key$1	USPAT; IBM_TDB	OR	OFF	2005/05/10 18:00
L7	488	l6 near8 (transform$8 re-encrypt$4 reencrypt$4 re-encipher$8 reencipher$8 re-cipher$7 recipher$8)	USPAT; IBM_TDB	OR	OFF	2005/05/10 18:01
L8	279	l1 and l7	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:37
L9	274	l8 and ((secret$2 private$1) near2 key$1)	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:39
L10	268	l9 and (decrypt$4 decipher$8 decod$3)	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:40
L11	2365	(decrypt$4 decipher$8 decod$3) near6 ((private$2 secret$2) near2 key$1)	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:40
L12	1260	l11 near8 (public$2 near key$1)	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:40
L13	151	l10 and l12	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:41
L14	704	(grant$3 sender$1 server$2) near3 ((secret$2 private$1) near key$1)	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:41
L15	206	l14 with l2	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:41
L16	128	l15 with (encrypt$4 encipher$8 cipher$8 transform$8 re-encrypt$4 reencrypt$4 re-encipher$8 reencipher$8 re-cipher$7 recipher$8)	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:42
L17	101	l16 and l1	USPAT; IBM_TDB	OR	OFF	2005/05/10 17:43